<u>IDLEWOOD</u>

ELECTRIC SUPPLY INC



March 2024

COOPER Lighting

Com**Ed** Energy Efficiency Program

Metalux

4SLSTPSLC-UNV

- Lumen packages for the most common striplight applications
- · 8ft, 4ft and 2ft lengths
- · Excellent performance up to 1375/foot and 125 LPW
- · Continuous frost white polycarbonate lens for even illumination
- CCT: 3500K, 4000K, and 5000K
- . Two driver options: UNV (0 to 10V) or 120V (Phase-cut) dimming
- UNV (DLC listed), 120V (Energy Star listed)
- Decorative end caps and J-box cover included
- · Selectable CCT and Lumen option for greater project flexibility
- Individual or continuous row mount with aligner or connector accessory

\$51.25

Metalux

8SLSTPSLC-UNV

- Lumen packages for the most common striplight applications
- 8ft, 4ft and 2ft lengths
- Excellent performance up to 1375/foot and 125 LPW
- Continuous frost white polycarbonate lens for even illumination
- CCT: 3500K, 4000K, and 5000K
- . Two driver options: UNV (0 to 10V) or 120V (Phase-cut) dimming
- UNV (DLC listed), 120V (Energy Star listed)
- Decorative end caps and J-box cover included
- Selectable CCT and Lumen option for greater project flexibility
- · Individual or continuous row mount with aligner or connector accessory

\$91.50

Metalux

4NWS3C3-NUV

- Offered in 2' and 4' lengths at 2 1/8" depth
- Selectable CCT in 3500K, 4000K, 5000K at 80 CRI
- · Selectable lumens in Low, Medium, and High up to 5,000 lumens
- Ideal for replacing two or three lamp fluorescent wraps
- 0-10V dimming with 120-277V (UNV) standard
- Suitable for ceiling, wall, or suspension mounting
- DLC Compliant and UL Damp rated
- Phase cut 120V Triac dimming option available
- Microwave motion sensor option available
- 5 year warranty

\$56.00