

# IDLEWOOD

ELECTRIC SUPPLY INC



**LITHONIA LIGHTING®**

an **AcuityBrands** company

**March 2024**

**ComEd**  
Energy Efficiency Program

## CPHB LED High Bay



### FEATURES & SPECIFICATIONS

**INTENDED USE** — Ideal one-for-one replacement of conventional lighting systems such as HID and fluorescent. For use in light industrial applications such as, warehousing and other large indoor spaces with mounting heights ranging from 10' – permitted.

**CONSTRUCTION** — Extruded aluminum channels enable superior thermal performance. Glare Control acrylic lens diffuses light source and reduces glare while protecting LEDs. Lens meets DLC 5.1 standards for UGR (Unified Glare Rating).

**ELECTRICAL** — 70% lumen maintenance at > 100,000 hours. Thermally protected driver standard with 0-10V dimming. Luminaire surge protection level: designed to withstand up to 6kV/3kA per ANSI C82.77-5-2015 Multi-volt driver, 120-277V standard.

**INSTALLATION** — Fixture is suitable for mounting by chain, cable, surface-mount bracket, pendant monopoint, or hook monopoint. Designed for use in ambient temperatures ranging from -40°C to 55°C when suspended 18" off ceiling. Surface mount to 45°C ambient operation.



<b>CPHB 12LM MVOLT 4/5K</b>	<b>CPHB 15LM MVOLT 4/5K</b>
<b>\$99.00</b>	<b>\$109.00</b>

(While supplies last)